# **NYT 630**

### **DESCRIPTION**

- · Industrial protective supported glove.
- Supported glove knitted glove with synthetic filament.
- · Latex knit wrist to ensure snug fit.
- 4 sizes available: 7, 8, 9 and 10.
- Trade unit: 10 pairs, 200 pairs in a transit case.

## **CHARACTERISTICS**

- Seamless non stop process for extra strength.
- Made from 100% polyamid continuous thread.
- Stretchable nitrile rubber coating on palm and finger tips.

## **PERFORMANCES**

- · Excellent comfort and dexterity.
- · Low lint glove.
- Good abrasion resistance.
- Coating resistant to oils and greases.
- In compliance with standards EN420 (General requirements) and EN388 (Mechanical risks) by the notified laboratory CTC, Centre Technique Cuir Maroquinerie, Lyon.

## **APPLICATIONS**

- For fine tactile handling, finishing work, light assembly and packing in dry or dirty environments.
- · Photographic laboratory.
- · Light handling works.
- Quality control.

## **LIMITATIONS**

- Do not use for handling liquids.
- · Limited protection at the wrist.



This glove is certified to comply with the essential requirements of European Directive EEC/89/686 of December 21rst, 1989 relative to personal protective equipment submitted to CE type examination issued by a notified laboratory, who certifies the conformity of this glove with the EN standards to which it responds and certifies the performance levels obtained during tests.





LIV 420

EN 420 5 Dexterity

EN 388

4 Abrasion

1 Cut

2 Tear

1 Puncture



Order codes

 Sizes
 7 (S)
 8 (M)
 9 (L)
 10 (XL)

 NYT 630
 1711E01000
 1711E02000
 1711E03000
 1711E04000



N° CMS/TDS/NYT630EN/FT/5 - 30/08





