Nitrotough N120

DESCRIPTION

- · Industrial protective glove.
- Nitrile supported glove.
- 4 sizes available: 7, 8, 9 and 10.
- Trade unit: 12 pairs, 144 pairs in a transit case.

CHARACTERISTICS

- Seamless nylon liner, gauge 13.
- Smooth nitrile three-quarter dip coating.
- Fine and stretchable stitches for excellent comfort.
- · Latex knit wrist to ensure snug fit.

PERFORMANCES

- High flexibility and dexterity for an optimum comfort in use.
- Excellent abrasion resistance.
- Covered in a layer resistant to polluted pieces being handled.
- In compliance with the standards EN420 (General requirements) and EN388 (Mechanical Hazards) by the notified laboratory CTC - Centre Technique du Cuir.

APPLICATIONS

- For all type of work requiring a good dexterity.
- Construction, general handlings.

LIMITATIONS

· Do not use for handling liquids or pointed objects.



This glove is certified to comply with the essential requirements of European Directive EEC/89/686 of December 21rst, 1989 relative to personal protective equipment submitted to CE type examination issued by a notified laboratory, who certifies the conformity of this glove with the EN standards to which it responds and certifies the performance levels obtained during tests.





EN 420 5 Dexterity

4121

EN 388 Mechanical hazards EN 388

- 4 Abrasion
- 1 Cut
- 2 Tear1 Puncture

Order codes 8 (M)

7 (S) 8 (M)M9999100
M9999101

9 (L) M9999102 10 (XL) M9999103



Sizes

Nitrotough N120



