

Nitrotough N1200&N1300

DESCRIPTION

- Industrial protective glove.
- Nitrile supported glove.
- 3/4 dipped (N1200) or fully dipped (N1300).
- 4 sizes available : 7, 8, 9 and 10.
- Trade unit : 12 pairs, 144 pairs in a transit case.

CHARACTERISTICS

- Seamless nylon liner, gauge 13.
- Smooth nitrile coating.
- Fine and stretchable stitches for excellent comfort.
- Latex knit wrist ensures snug fit.
- Compliant with Oeko-Tex® Standard 100 which is a global uniform testing and certification system which attests the ecological properties of the gloves.
- European Directive compliant for food contact.

PERFORMANCES

- High flexibility and dexterity for an optimum comfort in use.
- Excellent abrasion resistance.
- Covered in a layer resistant to polluted pieces being handled.
- In compliance with the standards EN420 (General requirements) and EN388 (Mechanical Hazards) by the notified laboratory CTC - Centre Technique du Cuir.
- Compliant with Oeko-Tex® Standard 100.

APPLICATIONS

- For all type of work requiring a good dexterity : construction, general engineering, food handlings...

LIMITATIONS

- Do not use for handling liquids.
- Do not use for handling fatty foods.



This glove is certified to comply with the essential requirements of European Directive EEC/89/686 of December 21st, 1989 relative to personal protective equipment submitted to CE type examination issued by a notified laboratory, who certifies the conformity of this glove with the EN standards to which it responds and certifies the performance levels obtained during tests.



EN 420

EN 420

5 Dexterity

EN 388

4 Abrasion

1 Cut

2 Tear

1 Puncture



EN 388

Mechanical hazards



Order codes

Sizes

Nitrotough N1200
Nitrotough N1300

7 (S)

200N12007
200N13007

8 (M)

200N12008
200N13008

9 (L)

200N12009
200N13009

10 (XL)

200N12000
200N13000