Nitrotough N1500&N1700

DESCRIPTION

- Industrial protective glove.
- Nitrile supported glove.
- 3/4 dipped (N1500) or fully dipped (N1700).
- 4 sizes available: 7, 8, 9 and 10.
- Trade unit: 12 pairs, 144 pairs in a transit case.

CHARACTERISTICS

- Seamless nylon liner, gauge 13.
- Rough nitrile coating.
- Fine and stretchable stitches for excellent comfort.
- · Latex knit wrist ensures snug fit.
- Compliant with Oëko-Tex® Standard 100 which is a global uniform testing and certification system which attests the ecological properties of the gloves.
- European Directive compliant for food contact.

PERFORMANCES

- High flexibility and dexterity for an optimum comfort in use.
- Excellent abrasion resistance.
- Covered in a layer resistant to polluted pieces being handled.
- In compliance with the standards EN420 (General requirements) and EN388 (Mechanical Hazards) by the notified laboratory CTC - Centre Technique du Cuir.
- Compliant with Oëko-Tex® Standard 100.

APPLICATIONS

 For all type of work requiring a good dexterity: construction, general engineering, food handlings...

LIMITATIONS

- Do not use for handling liquids.
- · Do not use for handling fatty foods.



This glove is certified to comply with the essential requirements of European Directive EEC/89/686 of December 21rst, 1989 relative to personal protective equipment submitted to CE type examination issued by a notified laboratory, who certifies the conformity of this glove with the EN standards to which it responds and certifies the performance levels obtained during tests.





EN 420

5 Dexterity

EN 388

4 Abrasion

1 Cut

2 Tear

1 Puncture



EN 388

Mechanical hazards

Order codes

 Sizes
 7 (S)
 8 (M)
 9 (L)
 10 (XL)

 Nitrotough N1500
 200N15007
 200N15008
 200N15009
 200N15000

 Nitrotough N1700
 200N17007
 200N17008
 200N17009
 200N17000





